

How to add a prebuilt .ko

1. Step1: Make ko(Ex: abc.ko)

Note: Prebuilt files should use the same toolchain with BOOT image.

2. Step2: Add ko

```
# PREBUILT_KO_PATH = "./meta/meta-mediatek-aud/recipes-kernel/modules/files \
    /prebuilt-modules/lib/modules/4.4.22 "
# PREBUILT_KO_PKG_PATH = "./meta/meta-mediatek-aud/recipes-kernel/modules/files"
# PREBUILT_KO_CONF_PATH = "./meta/meta-mediatek-aud/recipes-kernel/modules/files \
    /prebuilt-modules/etc/modules-load.d "
```

```
$ cp ./abc.ko ${PREBUILT_KO_PATH} // put prebuilt ko into PREBUILT_KO_PATH.
```

3. Step3: Add ko start mode

- Ko auto start during bootup, add conf file that with ko name as it's content.

```
$ cd ${PREBUILT_KO_CONF_PATH}
```

```
$ touch abc.conf
```

```
$ vim abc.conf //write ko name(abc) into it, ko name is the content of abc.conf
```

```
$ :wq
```

- Ko start manually after bootup.

Nothing to do here, please insmod ko manually.

4. Step4: Make tar ball

```
$ cd ${PREBUILT_KO_PKG_PATH}
```

```
$ rm prebuilt-modules.tar.xz // remove the old prebuilt tar ball.
```

```
$ tar Jcvf prebuilt-modules.tar.xz prebuilt-modules //create a new one.
```

5. Compile

```
$ bitbake prebuilt-modules -c cleansstate
```

```
$ bitbake mtk-image-audio-8516
```

6. For example.

```
./meta/meta-mediatek-aud/recipes-kernel
├── linux
│   ├── linux-aud_4.4.bb
│   └── modules
│       ├── files
│       │   ├── prebuilt-modules
│       │   │   ├── etc
│       │   │   │   ├── modules-load.d
│       │   │   │   │   ├── as9050.conf
│       │   │   │   │   ├── snd-soc-tlv320.conf
│       │   │   │   │   └── tas5751.conf
│       │   │   └── lib
│       │   │       ├── modules
│       │   │       │   ├── 4.4.22
│       │   │       │   │   ├── as9050.ko
│       │   │       │   │   ├── snd-soc-tlv320.ko
│       │   │       │   │   └── tas5751.ko
│       │   └── prebuilt-modules.tar.xz
│       └── prebuilt-modules.bb
```

```
DESCRIPTION="install prebuilt ko"
LICENSE="GPLv2"
inherit bin_package

PN='prebuilt-modules'
S="${WORKDIR}/${PN}"

SRC_URI=" \
    file://prebuilt-modules.tar.xz \
"

FILES_${PN}-dev=""
FILES_${PN} += "/lib/modules /etc/modules-load.d"
INHIBIT_PACKAGE_STRIP = "1"
```